

| type number | A (mm) | B (mm) | H (mm) | thickness of metal sheet (mm) | weight (kg/pc) | 🔥 |
|---------------------|-----------|-----------|-----------|--|-------------------|---|
| NVO 90X62_S | 62 | 222 | 12 | 0,55 | 0,14 | 🔥 |
| NVO 90X62_F | | | | 0,6 | 0,18 | 🔥 |
| NVO 90X125_S | 125 | 285 | 12 | 0,55 | 0,29 | 🔥 |
| NVO 90X125_F | | | | 0,8 | 0,49 | 🔥 |
| NVO 90X250_S | 250 | 410 | 12 | 0,55 | 0,67 | 🔥 |
| NVO 90X250_F | | | | 0,8 | 1,15 | 🔥 |
| NVO 90X500_S | 500 | 660 | 15 | 0,7 | 1,62 | 🔥 |
| NVO 90X500_F | | | | 0,8 | 2,18 | 🔥 |



product description: This cover is used to cover the elbow 90°. To fix the cover use cover fixtures VU or NUV. For the elbow cover NVO 90X500 the outer right angle is replaced by skewed cut. These items can also be ordered in a varnished version.

surface finish: S - Pre-Galvanized according to EN 10346, EN 10143, zinc-layer 15-27 µm
F - Hot Dip Galvanized according to ČSN EN ISO 1461, zinc-layer 45 µm (min. 35 µm)

sales amount: 1 pc

certification: ČSN EN 61537:02

classification 🔥: ČSN 73 0895 P 90-R
DIN 4102-12E 90
STN 92 0205PS 90
Fire classification depends on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.
🔥 products are approved for non-standard constructions

